

Scandinavia Corn Roast Tractor Pull Rules 2025

2 Hooks Per Tractor Limit

1. **FOR SAFETY REASONS-NO ONE OTHER THAN DRIVER ALLOWED ON TRACTOR ANYWHERE ON SHOW GROUNDS!**
2. No alcoholic beverages on track or pit area. Any driver believed to be a potential safety hazard will be disqualified.
3. Tractors must be operated in a safe manner at all times. Anyone driving recklessly will be disqualified.
4. Anyone caught tampering with someone else's tractor will be disqualified.
5. One pull allowed per tractor in each class unless the track judge rules otherwise or if a tie is declared in the top placing tractors. If disqualification is ruled on top placing tractor, all other tractors move up one place.
6. Any tractor violating the track boundary will be disqualified. The decision of the track judge will be final.
7. Drivers must be 14 years of age or older. All drivers enter at own risk. Drivers between the age of 14 and 18 must have parent's written consent and safety class certificate with them. **NO EXCEPTIONS!!!**
8. Tractors will be stopped if the front end raises higher than the track judge decides is safe.
9. Extra weights must be securely fastened to the tractor. No weights allowed on platform. If anything falls off before the pin is pulled, the tractor will be disqualified.
10. Any gas-operated tractor must use gasoline only.
11. While pulling, the driver must remain on the seat with one hand on the wheel. No jumping or bouncing will be allowed, however, leaning will be permitted.
12. Tractors must stop immediately upon red flag signal from the judge or be disqualified. If puller is stopped by track judge for any reason, puller takes the distance where he/she stopped except if it is in the first 50 feet. If stopped within the first 50 feet, puller may be entitled to a restart.
13. Tractors must be wheel driven, no crawlers or dual wheels. No FWD.
14. Puller must furnish their own clevis or pullers' eye to accept eliminators hook. **(MINIMUM 2.5" HOLE. PULLING POINT CAN BE NO MORE THAN 1.5" FROM THE BACK OF HITCHING DEVICE.)**
15. All weight classes are allowed 25# overage.
16. In paced classes if the horn honks, even slightly, after the eliminator goes past the 100' mark the pull is disqualified.

**TRACK JUDGES RULING IS FINAL ON ALL AREAS OF DISPUTE NOT COVERED IN THESE RULES!
ANY BELLIGERENT BEHAVIOR WILL RESULT IN IMMEDIATE DISQUALIFICATION.**

PURE STOCK PACE 3.0 MPH

1. Must be 1957 or older.
2. **Any tractor that pulls in Pure Stock must remain Pure Stock if pulled in other classes. Pure Stock rules will apply to that tractor. No adding of weight brackets for another class.**
3. Weight Classes: 3400, 3700, 4000, 4700, 5000, 5500, 6000, 6500, 7000.
4. Maximum tire size: **3400-3999** 13.6" X 38"; **4000-4999** 14.9" X 38"; **5000-5999** 15.5" X 38"; **6000-6999** 16.9" X 38" **7000 and up** 18.4" X 38" or equivalent square inches.
5. Engine = Stock Block, Head, Manifold, Carb (by part number), no add-on parts not in original parts book. No electronic ignitions-stock coil only. Must have stock HP & RPM's.
6. Rigid draw bar mounted in stock location must not exceed 20" in height, nor closer than 28" to center of rear axle.
7. Tractors must have stock appearance.
8. **No cut or sharpened tires.**
9. Must use original air cleaner **ONLY** and must be hooked up.
10. **No weight brackets. NTPA style wheelie bars will be allowed.** All weights must be bolted directly to the wheel and rotate with the wheel. Ready Rod is acceptable. **A weight bracket is considered anything welded or fabricated to support or hold a weight.**

11. No shifting on the go (T/A).

NEAR STOCK PACE 4.0 MPH

1. Must be 1957 or older.
2. Weight Classes: 3400, 3700, 4000, 4700, 5000, 5500, 6000, 6500, 7000, 7600, & UNLIMITED.
3. Maximum Tire Size: **3400-3999** 13.6" X 38"; **4000-4999** 14.9" X 38"; **5000-5999** 15.5" X 38" **6000-6999** 16.9" X 38" **7000 and up** 18.4" X 38" or equivalent square inches.
4. Aftermarket air cleaner allowed.
5. Sharpened tires allowed-**Top Only**.
6. Weight brackets will be allowed.
7. Front weights shall not exceed more than 24" beyond the center of the front frames out most casting. Rear weight not to exceed 24" behind the center of the rear axle.
8. Rigid drawbar mounted in stock location must not exceed 20" in height, nor can it be closer than 18" from the centerline of the rear axle.
9. Engine speed must be controlled by the throttle lever and a functional stock governor only. No strings, wires, or foot feeds allowed.
10. Fenders are mandatory. Wheelie bars, kill switches are recommended but not mandatory.
11. Tractors must have stock appearance, stock sheet metal, block, transmission, rear end, etc.
12. No shifting on the go (T/A).

IMPROVED PACE 5.0 MPH

1. Must be 1957 or older.
2. Weight Classes: 3750, 4250, 4750, 5750, 6250, 6750.
3. Sharpened tires are allowed.
4. Fenders are Mandatory. Wheelie bars and kill switch recommended.
5. Max Tire Size: **3750 to 4750** 16.9" X 38" **5750 and up** 18.4" X 38".
6. Front weights shall not exceed 24" beyond the center of the front frames outmost casting. Rear weights not to exceed 24" behind the center of the rear axle.
7. Rigid draw bar shall not exceed 20" in height nor closer than 18" from the center of the rear axle.
8. Engine speed must be controlled by the throttle lever and a functional governor only. No strings, wires, or foot feeds allowed. 20% over RPM's will be allowed.
9. No shifting on the go (T/A).
10. **If tractor is equipped with a roll bar, the driver must wear a DOT approved helmet.**

MODIFIED PACE 7.0 MPH

1. Must be 1957 or older.
2. Weight Classes: 3750, 4250, 4750, 5750, 6750.
3. **3750 to 4750** 16.9" X 38" **5750 to 6750** 18.4" X 38".
4. Must run stock block, transmission, rear end, sheet metal for that make and model.
5. Cut tires are allowed.
6. Wheelie bars, kill switch and fenders are MANDATORY!
7. RPM's over 20% must have safety equipment (safety blanket, scatter shield, steel flywheel, fan shroud or side shields, etc.)
8. No shifting on the go (T/A).
9. **If equipped with a roll bar, you must wear a DOT approved helmet.**

FARM PULLING RULES

1. Any year farm tractor allowed.
2. Anyone caught tampering with another tractor will be disqualified.
3. Tractors must be operated in a safe manor at all times.
4. No crawlers, tire chains or duals.
5. Hitch point cannot be higher than 20" or closer than 18" from the center of the rear axle. All 3 point hitches must be locked from moving! **ABSOLUTELY NO FLOATING DRAWBARS!**
6. Any tractor violating track boundaries must take distance at that point.
7. Tractors must stop upon red flag or will be disqualified. If track judge stops pull for any reason, puller must take that distance.
8. Any driver's between 14-18 years old MUST have parental signature and tractor safety class certificate with them, **NO EXCEPTIONS!**
9. If anything falls off the tractor before the pin is pulled, tractor will be disqualified.

TRACK JUDGES RULING IS FINAL ON ALL AREAS OF DISPUTE NOT COVERED IN THESE RULES!

STOCK FARM CLASS PACE 6.0 MPH

1. Weight Classes: 8500, 9000, 9500, 10500, 12500, 14500.
2. Must be a "farm" tractor, for example: original frame, rear-end, trans, PTO, etc., installed & working.
3. Stock injection pump, stock turbo, tractor must have been factory equipped with turbo if one is installed.
4. No water injection.
5. Stock engine RPM's only!
6. 20.8" max width on 9000# and over. No cut or sharpened tires! (True road worn is OK.)
7. No FWD or front wheel assist unless unhooked or turned off.
8. TA's or shift on the go is OK.
9. No Alcohol. Must run on gas, LP or diesel. Must run the fuel it was originally designed for.

IMPROVED FARM CLASS PACE AS AGREED AT DRIVERS MEETING

1. Weight Classes: 9500, 10500, 11000, 12500.
2. Turbo-limited to single turbo, no larger than 3" on inlet (no Bigfoot exhaust housing).
3. 3000 RPM Max! Anyone caught over will be disqualified.
4. 20.8" max width tire size. Cut tires are OK.
5. **ALL TRACTORS MUST HAVE SAFETY EQUIPMENT**-Wheelie bars, air shut-off, fire extinguisher, cross bolts in exhaust is strongly recommended. Two 3/8" bolts, 90 degrees X 1.0" apart, no more than 10" from turbo outlet.
6. No component tractors-MUST run AG rear-end.
7. No rain caps or curved exhaust pipes (vertical discharge only).