

Scandinavia Corn Roast Tractor Pull Rules 2026

2 Hooks Per Tractor Limit

Sunday

GENERAL RULES

1. **FOR SAFETY REASONS - NO ONE OTHER THAN DRIVER ALLOWED ON TRACTOR ANYWHERE ON SHOW GROUNDS!**
2. Tractors must be operated in a safe manner on and off the track at all times.
3. Tractors must stop upon red flag signal.
4. While pulling, the driver must remain on the seat with one hand on the wheel. No jumping or bouncing is allowed; however, leaning is permitted.
5. One restart is allowed within the first 50 feet.
6. Drivers must be 12 years of age or older. All drivers enter at own risk. Drivers between the age of 12 and 17 must have parent's written consent and safety class certificate with them.
7. Tractors must be wheel driven, no crawlers or dual wheels, NO FWD.
8. Weights must be securely fastened to the tractor. If anything falls off before being unhooked, the pull is disqualified.
9. Puller must furnish their own clevis or pullers' eye to accept eliminators hook.
10. In paced classes If the horn honks, even slightly, after the eliminator operator goes past the 100' mark the pull ends.
11. Pure Stock allowed 100 lbs. overage, all other classes 50 lbs.
12. Any suspected rule violations must be reported prior to that tractor pulling.
13. Track Official's decisions are final.

PURE STOCK PACE 3.0 MPH

1. Must be 1957 or older.
2. **Any tractor that pulls in Pure Stock must remain Pure Stock if pulled in other classes. Pure Stock rules will always apply to that tractor. No adding of weight brackets for another class.**
3. Weight classes: 3500 (13.6), 4000 (15.5), 5000 (15.5), 6000 (16.9), 7000 (18.4).
4. Engine: stock block, head, manifold, carb, no electronic ignitions, (under cap Petronix ok), stock coil only, stock hp and rpms.
5. Tractors must appear stock. No aftermarket fuel tanks, lightweight front ends, aluminum wheels, air-cleaners, etc.
6. Factory drawbars only. 18" max hitch height.
7. No cut or sharpened tires.
8. **No weight brackets.** All wheel weights must be bolted directly to the wheel and rotate with the wheel. A weight bracket is anything welded or fabricated to support or hold a weight.
9. Wheelie bars and other safety equipment is allowed.
10. No shifting on the go (T/A).

NEAR STOCK PACE 4.0 MPH

1. Must be 1957 or older.
2. Weight classes: 3500 (13.6), 4000 (15.5), 5000 (15.5), 6000 (16.9), 7000 (18.4) & UNLIMITED.
3. After market air cleaner is allowed.
4. Sharpened tires allowed - **Top Only**.
5. Front weights shall not exceed more than 24" beyond the center of the front frames out most casting. Rear weight not to exceed 24" behind center rear axle.
6. Rigid drawbar mounted in stock location must not exceed 20" in height nor can it be closer than 18" from the center line of the rear axle.
7. Engine speed must be controlled by the throttle lever and a functional stock governor only. No strings, wires or foot feeds allowed.
8. Fenders are mandatory. Wheelie bars, kill switches, recommended, but not mandatory.
9. Tractors must have stock appearance, stock sheet metal, block, transmission, rear end, etc.
10. No shifting on the go (T/A).

STOCK FARM CLASS PACE 6.0 MPH

1. Weight classes: 8500, 10500.
2. Must be a "farm" tractor, for example: original frame, rear-end, trans, PTO, etc. Installed & working.
3. All 3-point hitches must be locked from moving! **ABSOLUTELY NO FLOATING DRAWBARS!!!!**
4. Stock injection pump, stock turbo, tractor must be factory equipped with turbo.
5. No water injection.
6. Stock engine RPM's only!
7. No cut or sharpened tires!
8. No FWD or front assists unless unhooked or turned off.
9. TA's shift on the go is ok.
10. No Alcohol. Must run on gas, LP or diesel. Must run the fuel it was originally designed for.

IMPROVED FARM CLASS PACE AS AGREED AT DRIVER'S MEETING

1. Weight classes: 9500, 10500, 11000, 12500.
2. Turbo - limited to single turbo, no larger than 3" on inlet (no Bigfoot exhaust housing).
3. 3000 RPM Max! Anyone caught over will be disqualified.
4. 20.8 max width tire size. Cut tires are ok.
5. **ALL TRACTORS MUST HAVE SAFETY EQUIPMENT** - Wheelie bars, air shut-off, fire extinguisher, cross bolts in exhaust is strongly recommended. Two 3/8" bolts, 90 Deg. x 1" apart, no more than 10" from turbo outlet.
6. No component tractors - Must run an AG rear-end.
7. No rain caps or curved exhaust pipes (vertical discharge only).